



CL 07

Technical Data Sheet

Description:

Cleaner, degreaser and stripper

Usage:

Used for cleaning application equipment, cleaning wet or dry waterborne paints drips, degreasing surfaces before application of any type of paint and removal of old paint, dip for long enough. Applying by the a spray-gun, a brush or a towel. After short effect of CL 07, the surface must be wiped with a clean and dry towel. Depending in the degree of grease use a new towel. After use CL 07 rinse the surface with clean water! Do not use to adjust the viscosity of paints. CL 07 does not contain either acids or alkalies.

Colours:

0000 - bezbarvý, namodralý

Specific gravity: (ČSN EN ISO 2811-1)

1,09 g/cm³

Application conditions:

Use the protective equipment during greasing and cleaning. Before use read carefully the recommendations in the safety data sheet. Close a surface or a canister with CL 07 after use protecting your health and preventing excessive damage to the environment.

Storage:

in the original unopened packaging at temperatures between +5°C and +25°C.

Packaging in l:

1; 5

Notes:

DFT - dry film thickness
WFT - wet film thickness

MS - medium dry matter
HS - high dry matter

GU - Gloss Unit
KU - Krebs unit of viscosity

All information given in this technical data sheet are based on our best knowledge, laboratory test results and practical experience to the date specified below. According to the fact that the conditions of the product's use are out of our control, we can only guarantee the product quality itself. As a producer we cannot be responsible for damage arising from the use of the products without following above recommended instructions or for improper purposes. We reserve the right to change above specified information without prior notice. Always request the actual version of the product data sheet. This technical data sheet replaces all previously released. The validity of the data provided here will be terminated automatically after five years.

