


SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier:** TIXODECOR
Other means of identification:
UFI: AE20-Y0UG-U006-AW4U
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**
 Relevant uses: Paint
 Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**
 VITON s.r.o.
 Planá 90
 37001 České Budějovice - Czech Republic
 Phone: +420 381 581 022
 info@viton.cz
 www.viton.cz
- 1.4 Emergency telephone number:** Toxikologické informační středisko, Na bojišti 1, Prague, Phone: non-stop +420 224 919 293 or +420 224 915 402

SECTION 2: HAZARDS IDENTIFICATION **

- 2.1 Classification of the substance or mixture:**
CLP Regulation (EC) No 1272/2008:
 Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.
 Aquatic Acute 1: Hazardous to the aquatic environment, acute hazard, Category 1, H400
 Aquatic Chronic 1: Hazardous to the aquatic environment, long-term hazard, Category 1, H410
 Flam. Liq. 3: Flammable liquids, Category 3, H226
 Skin Sens. 1A: Sensitisation, skin, Category 1A, H317
 STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336
- 2.2 Label elements:**
CLP Regulation (EC) No 1272/2008:
Warning
- 
- Hazard statements:**
 Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.
 Flam. Liq. 3: H226 - Flammable liquid and vapour.
 Skin Sens. 1A: H317 - May cause an allergic skin reaction.
 STOT SE 3: H336 - May cause drowsiness or dizziness.
- Precautionary statements:**
 P101: If medical advice is needed, have product container or label at hand.
 P102: Keep out of reach of children.
 P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P280: Wear protective gloves/face protection/protective clothing/respiratory protection/protective footwear.
 P302+P352: IF ON SKIN: Wash with plenty of water.
 P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P370+P378: In case of fire: Use ABC powder extinguisher to extinguish.
 P501: Dispose of the contents/containers in accordance with the current legislation on waste treatment
- Supplementary information:**
 EUH066: Repeated exposure may cause skin dryness or cracking.
- Substances that contribute to the classification**
 Hydrocarbons, C9-C11,n-alkanes, iso-alkanes, cyclics, <2% aromatics; octhilonone (ISO) (CAS: 26530-20-1)
- UFI:** AE20-Y0UG-U006-AW4U

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -

SECTION 2: HAZARDS IDENTIFICATION ** (continued)

2.3 Other hazards:

Product fails to meet PBT/vPvB criteria
Endocrine-disrupting properties: The product fails to meet the criteria.

** Changes with regards to the previous version

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS **

3.1 Substance:




Non-applicable

3.2 Mixture:

Chemical description: Mixture of substances

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification		Concentration
CAS: Non-applicable EC: 919-857-5 Index: Non-applicable REACH: 01-2119463258-33-XXXX	Hydrocarbons, C9-C11,n-alkanes, iso-alkanes, cyclics, <2% aromatics⁽¹⁾	Self-classified	25 - <50 %
	Regulation 1272/2008	Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H336; EUH066 - Danger 	
CAS: 34590-94-8 EC: 252-104-2 Index: Non-applicable REACH: 01-2119450011-60-XXXX	Dipropylene Glycol Methyl Ether⁽²⁾	Not classified	1 - <3 %
	Regulation 1272/2008		
CAS: 26530-20-1 EC: 247-761-7 Index: 613-112-00-5 REACH: 01-2120768921-45-XXXX	octhilinone (ISO)⁽¹⁾	ATP ATP15	0,1 - <1 %
	Regulation 1272/2008	Acute Tox. 2: H330; Acute Tox. 3: H301+H311; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Eye Dam. 1: H318; Skin Corr. 1: H314; Skin Sens. 1A: H317; EUH071 - Danger 	
CAS: 123-86-4 EC: 204-658-1 Index: 607-025-00-1 REACH: 01-2119485493-29-XXXX	N-butyl acetate⁽²⁾	ATP CLP00	<0,1 %
	Regulation 1272/2008	Flam. Liq. 3: H226; STOT SE 3: H336; EUH066 - Warning 	

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

⁽²⁾ Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Other information:

Identification	M-factor	
	octhilinone (ISO) CAS: 26530-20-1 EC: 247-761-7	Acute
	Chronic	100

Identification	Specific concentration limit
octhilinone (ISO) CAS: 26530-20-1 EC: 247-761-7	% (w/w) >=0,0015: Skin Sens. 1A - H317

** Changes with regards to the previous version

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

- CONTINUED ON NEXT PAGE -

SECTION 4: FIRST AID MEASURES (continued)

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES**5.1 Extinguishing media:****Suitable extinguishing media:**

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO₂).

Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES**6.1 Personal precautions, protective equipment and emergency procedures:****For non-emergency personnel:**

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

- CONTINUED ON NEXT PAGE -

SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

- Minimum Temp.: 5 °C
- Maximum Temp.: 25 °C
- Maximum time: 24 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification	Occupational exposure limits		
	IOELV (8h)	50 ppm	308 mg/m ³
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	IOELV (STEL)		
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	IOELV (8h)	50 ppm	241 mg/m ³
	IOELV (STEL)	150 ppm	723 mg/m ³

DNEL (Workers):

- CONTINUED ON NEXT PAGE -

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	283 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	308 mg/m ³	Non-applicable
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	11 mg/kg	Non-applicable	11 mg/kg	Non-applicable
	Inhalation	600 mg/m ³	600 mg/m ³	300 mg/m ³	300 mg/m ³

DNEL (General population):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	Oral	Non-applicable	Non-applicable	36 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	121 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	37,2 mg/m ³	Non-applicable
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	Oral	2 mg/kg	Non-applicable	2 mg/kg	Non-applicable
	Dermal	6 mg/kg	Non-applicable	6 mg/kg	Non-applicable
	Inhalation	300 mg/m ³	300 mg/m ³	35,7 mg/m ³	35,7 mg/m ³

PNEC:



Identification					
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	STP	4168 mg/L	Fresh water	19 mg/L	
	Soil	2,74 mg/kg	Marine water	1,9 mg/L	
	Intermittent	190 mg/L	Sediment (Fresh water)	70,2 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	7,02 mg/kg	
octhilinone (ISO) CAS: 26530-20-1 EC: 247-761-7	STP	Non-applicable	Fresh water	0,0022 mg/L	
	Soil	0,0082 mg/kg	Marine water	0,00022 mg/L	
	Intermittent	0,00122 mg/L	Sediment (Fresh water)	0,0475 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	0,00475 mg/kg	
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	STP	35,6 mg/L	Fresh water	0,18 mg/L	
	Soil	0,09 mg/kg	Marine water	0,018 mg/L	
	Intermittent	0,36 mg/L	Sediment (Fresh water)	0,981 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	0,098 mg/kg	

8.2 Exposure controls:



A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory respiratory tract protection	Filter mask for gases and vapours		EN 405:2002+A1:2010	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands



Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory hand protection	NON-disposable chemical protective gloves		EN ISO 374-1:2016+A1:2018 EN 16523-1:2015+A1:2018 EN ISO 21420:2020	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin.

- CONTINUED ON NEXT PAGE -





SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.



D.- Eye and face protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory face protection	Face shield		EN 166:2002 EN 167:2002 EN 168:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties		EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982-1:2004/A1:2010 EN ISO 6529:2013 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994	For professional use only. Clean periodically according to the manufacturer's instructions.
 Mandatory foot protection	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties		EN ISO 13287:2020 EN ISO 20345:2011 EN 13832-1:2019	Replace boots at any sign of deterioration.

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

- V.O.C. (Supply): 68 % weight
- V.O.C. density at 20 °C: 578 kg/m³ (578 g/L)
- Average carbon number: 9,91
- Average molecular weight: 145,79 g/mol

With regard to Directive 2004/42/EC, this product which is ready to use has the following characteristics:

- V.O.C. density at 20 °C: 578 kg/m³ (578 g/L)
- EU limit for the product (Cat. A.H): 750 g/L (2010)
- Components: Non-applicable

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

- Physical state at 20 °C: Liquid
- Appearance: Fluid
- Colour: According to the markings on the package

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Odour:	Characteristic
Odour threshold:	Non-applicable *
Volatility:	
Boiling point at atmospheric pressure:	120 - 285 °C
Vapour pressure at 20 °C:	183 Pa
Vapour pressure at 50 °C:	1656,44 Pa (1,66 kPa)
Evaporation rate at 20 °C:	Non-applicable *
Product description:	
Density at 20 °C:	850 kg/m ³
Relative density at 20 °C:	0,85
Dynamic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 20 °C:	510 mm ² /s
Kinematic viscosity at 40 °C:	Non-applicable *
Concentration:	Non-applicable *
pH:	Non-applicable *
Vapour density at 20 °C:	Non-applicable *
Partition coefficient n-octanol/water 20 °C:	Non-applicable *
Solubility in water at 20 °C:	Non-applicable *
Solubility properties:	Non-applicable *
Decomposition temperature:	Non-applicable *
Melting point/freezing point:	Non-applicable *
Flammability:	
Flash Point:	39 °C
Flammability (solid, gas):	Non-applicable *
Autoignition temperature:	265 °C
Lower flammability limit:	Not available
Upper flammability limit:	Not available
Particle characteristics:	
Median equivalent diameter:	Non-applicable

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties:	Non-applicable *
Oxidising properties:	Non-applicable *
Corrosive to metals:	Non-applicable *
Heat of combustion:	Non-applicable *
Aerosols-total percentage (by mass) of flammable components:	Non-applicable *

Other safety characteristics:

Surface tension at 20 °C:	Non-applicable *
Refraction index:	Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

- CONTINUED ON NEXT PAGE -

SECTION 10: STABILITY AND REACTIVITY (continued)

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

Contains glycols. It is recommended not to breathe the vapours for prolonged periods of time due to the possibility of effects that are hazardous to the health .

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Prolonged inhalation of the product is corrosive to mucous membranes and the upper respiratory tract

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for skin contact. For more information see section 3.
- Contact with the eyes: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
IARC: Hydrocarbons, C9-C11,n-alkanes, iso-alkanes, cyclics, <2% aromatics (3); Hydrocarbons, C10, aromatics, < 1% naphthalene (3); 2,6-di-tert-butyl-p-cresol (3); Solvent naphtha (petroleum), heavy arom (FP>60°C) (3); Hydrocarbons, C10-C13, aromatics, < 1% naphthalene (3); 2,6-di-tert-butyl-p-cresol (3); Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7 (3)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

E- Sensitizing effects:

- CONTINUED ON NEXT PAGE -

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.

F- Specific target organ toxicity (STOT) - single exposure:

Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

- Skin: Repeated exposure may cause skin dryness or cracking

H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
	Route	Value	
octhlinone (ISO) CAS: 26530-20-1 EC: 247-761-7	LD50 oral	125 mg/kg	
	LD50 dermal	311 mg/kg	
	LC50 inhalation	0,5 mg/L (ATEi)	
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	LD50 oral	>5000 mg/kg	Rat
	LD50 dermal	9510 mg/kg	Rabbit
	LC50 inhalation	>20 mg/L	
Hydrocarbons, C9-C11,n-alkanes, iso-alkanes, cyclics, <2% aromatics CAS: Non-applicable EC: 919-857-5	LD50 oral	>5000 mg/kg	Rat
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation	>20 mg/L	
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	LD50 oral	12789 mg/kg	Rat
	LD50 dermal	14112 mg/kg	Rabbit
	LC50 inhalation	23,4 mg/L (4 h)	Rat

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product fails to meet the criteria.

Other information

Non-applicable

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Acute toxicity:

Identification	Concentration		Species	Genus
	Route	Value		
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	LC50	10000 mg/L (96 h)	Pimephales promelas	Fish
	EC50	1919 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	Non-applicable		
octhlinone (ISO) CAS: 26530-20-1 EC: 247-761-7	LC50	>0.1 - 1 mg/L (96 h)		Fish
	EC50	>0.1 - 1 mg/L (48 h)		Crustacean
	EC50	>0.1 - 1 mg/L (72 h)		Algae
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	LC50	Non-applicable		
	EC50	Non-applicable		
	EC50	675 mg/L (72 h)	Scenedesmus subspicatus	Algae

- CONTINUED ON NEXT PAGE -

SECTION 12: ECOLOGICAL INFORMATION (continued)

Chronic toxicity:

Identification	Concentration		Species	Genus
	NOEC	Non-applicable		
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	NOEC	Non-applicable		
	NOEC	0,5 mg/L	Daphnia magna	Crustacean
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	NOEC	Non-applicable		
	NOEC	23,2 mg/L	Daphnia magna	Crustacean

12.2 Persistence and degradability:

Substance-specific information:

Identification	Degradability		Biodegradability	
	BOD5	Non-applicable	Concentration	Non-applicable
Hydrocarbons, C9-C11,n-alkanes, iso-alkanes, cyclics, <2% aromatics CAS: Non-applicable EC: 919-857-5	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	80 %
	BOD5	Non-applicable	Concentration	Non-applicable
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	COD	0 g O2/g	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	73 %
	BOD5	Non-applicable	Concentration	Non-applicable
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	COD	Non-applicable	Period	5 days
	BOD5/COD	Non-applicable	% Biodegradable	84 %
	BOD5	Non-applicable	Concentration	Non-applicable

12.3 Bioaccumulative potential:

Substance-specific information:

Identification	Bioaccumulation potential	
	BCF	Pow Log
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	BCF	1
	Pow Log	-0.06
	Potential	Low
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	BCF	4
	Pow Log	1.78
	Potential	Low

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
	Koc	Non-applicable	Henry	Non-applicable
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	2,478E-2 N/m (25 °C)	Moist soil	Non-applicable
	BOD5	Non-applicable	Concentration	Non-applicable

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product fails to meet the criteria.

12.7 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Dangerous

Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

Waste management (disposal and evaluation):

SECTION 13: DISPOSAL CONSIDERATIONS (continued)

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2021 and RID 2021:



- 14.1 UN number or ID number:** UN1263
- 14.2 UN proper shipping name:** PAINT
- 14.3 Transport hazard class(es):** 3
Labels: 3
- 14.4 Packing group:** III
- 14.5 Environmental hazards:** Yes
- 14.6 Special precautions for user**
Special regulations: 163, 367, 650
Tunnel restriction code: D/E
Physico-Chemical properties: see section 9
Limited quantities: 5 L
- 14.7 Maritime transport in bulk according to IMO instruments:** Non-applicable

Transport of dangerous goods by sea:

With regard to IMDG 40-20:



- 14.1 UN number or ID number:** UN1263
- 14.2 UN proper shipping name:** PAINT
- 14.3 Transport hazard class(es):** 3
Labels: 3
- 14.4 Packing group:** III
- 14.5 Marine pollutant:** Yes
- 14.6 Special precautions for user**
Special regulations: 223, 955, 163, 367
EmS Codes: F-E, S-E
Physico-Chemical properties: see section 9
Limited quantities: 5 L
Segregation group: Non-applicable
- 14.7 Maritime transport in bulk according to IMO instruments:** Non-applicable

Transport of dangerous goods by air:

With regard to IATA/ICAO 2023:

SECTION 14: TRANSPORT INFORMATION (continued)



- 14.1 UN number or ID number:** UN1263
- 14.2 UN proper shipping name:** PAINT
- 14.3 Transport hazard class(es):** 3
Labels: 3
- 14.4 Packing group:** III
- 14.5 Environmental hazards:** Yes
- 14.6 Special precautions for user**
Physico-Chemical properties: see section 9
- 14.7 Maritime transport in bulk according to IMO instruments:** Non-applicable

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Regulation (EC) No 528/2012: contains a preservative to protect the initial properties of the treated article. Contains octhilineone (ISO).
 Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable
 Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable
 Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable
 Article 95, REGULATION (EU) No 528/2012: octhilineone (ISO) (Product-type 6, 7, 8, 9, 10, 11, 13)
 REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
P5c	FLAMMABLE LIQUIDS	5000	50000
E1	ENVIRONMENTAL HAZARDS	100	200

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Shall not be used in:
 —ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
 —tricks and jokes,
 —games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION **

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

** Changes with regards to the previous version

SECTION 16: OTHER INFORMATION ** (continued)**COMPOSITION/INFORMATION ON INGREDIENTS (SECTION 3):**

- Removed substances
 - 2-butoxyethanol (111-76-2)
 - Cobalt bis(2-ethylhexanoate) (136-52-7)
 - 2-ethylhexanoic acid, zirconium salt (22464-99-9)
 - Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) (64742-82-1)

Substances that contribute to the classification (SECTION 2):

- Removed substances
 - Cobalt bis(2-ethylhexanoate) (136-52-7)
 - Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) (64742-82-1)

CLP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16):

- Pictograms
- Hazard statements

Texts of the legislative phrases mentioned in section 2:

H400: Very toxic to aquatic life.
H410: Very toxic to aquatic life with long lasting effects.
H317: May cause an allergic skin reaction.
H336: May cause drowsiness or dizziness.
H226: Flammable liquid and vapour.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Acute Tox. 2: H330 - Fatal if inhaled.
Acute Tox. 3: H301+H311 - Toxic if swallowed or in contact with skin.
Aquatic Acute 1: H400 - Very toxic to aquatic life.
Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.
Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.
Eye Dam. 1: H318 - Causes serious eye damage.
Flam. Liq. 3: H226 - Flammable liquid and vapour.
Skin Corr. 1: H314 - Causes severe skin burns and eye damage.
Skin Sens. 1A: H317 - May cause an allergic skin reaction.
STOT SE 3: H336 - May cause drowsiness or dizziness.

Classification procedure:

Aquatic Acute 1: Calculation method
Aquatic Chronic 1: Calculation method
Skin Sens. 1A: Calculation method
STOT SE 3: Calculation method
Flam. Liq. 3: Calculation method (2.6.4.3)

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

<http://echa.europa.eu>
<http://eur-lex.europa.eu>

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road
IMDG: International maritime dangerous goods code
IATA: International Air Transport Association
ICAO: International Civil Aviation Organisation
COD: Chemical Oxygen Demand
BOD5: 5day biochemical oxygen demand
BCF: Bioconcentration factor
LD50: Lethal Dose 50
LC50: Lethal Concentration 50
EC50: Effective concentration 50
LogPOW: Octanolwater partition coefficient
Koc: Partition coefficient of organic carbon
UFI: unique formula identifier
IARC: International Agency for Research on Cancer

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

TIXODECOR

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -