




SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier:** VIR.AC
Other means of identification:
UFI: KP20-GOWP-R00P-AWW1
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**
 Relevant uses: Additive for varnishes and paints
 Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**
 VITON s.r.o.
 Planá 90
 37001 České Budějovice - Czech Republic
 Phone: +420 381 581 022
 info@viton.cz
 www.viton.cz
- 1.4 Emergency telephone number:** Toxikologické informační středisko, Na bojišti 1, Prague, Phone: non-stop +420 224 919 293 or +420 224 915 402

SECTION 2: HAZARDS IDENTIFICATION

- 2.1 Classification of the substance or mixture:**
CLP Regulation (EC) No 1272/2008:
 Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.
 Flam. Liq. 3: Flammable liquids, Category 3, H226
 Repr. 1B: Reproductive toxicity, Category 1B, H360FD
 STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336
- 2.2 Label elements:**
CLP Regulation (EC) No 1272/2008:
 Danger
- 


- Hazard statements:**
 Flam. Liq. 3: H226 - Flammable liquid and vapour.
 Repr. 1B: H360FD - May damage fertility. May damage the unborn child.
 STOT SE 3: H336 - May cause drowsiness or dizziness.
- Precautionary statements:**
 P101: If medical advice is needed, have product container or label at hand.
 P102: Keep out of reach of children.
 P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P280: Wear protective gloves/face protection/protective clothing/respiratory protection/protective footwear.
 P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P308+P313: IF exposed or concerned: Get medical advice/attention.
 P370+P378: In case of fire: Use ABC powder extinguisher to extinguish.
 P501: Dispose of the contents/containers in accordance with the current legislation on waste treatment
- Supplementary information:**
 EUH066: Repeated exposure may cause skin dryness or cracking.
- Substances that contribute to the classification**
 N-butyl acetate (CAS: 123-86-4); Dibutyltin Dilaurate (CAS: 77-58-7)
- Additional Labelling (Annex XVII, REACH):**
 Restricted to professional users
UFI: KP20-GOWP-R00P-AWW1
- 2.3 Other hazards:**

SECTION 2: HAZARDS IDENTIFICATION (continued)

Product fails to meet PBT/vPvB criteria
Endocrine-disrupting properties: The product fails to meet the criteria.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:




Non-applicable

3.2 Mixture:

Chemical description: Mixture of substances

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification	Concentration
CAS: 123-86-4 EC: 204-658-1 Index: 607-025-00-1 REACH: 01-2119485493-29-XXXX	N-butyl acetate <input type="checkbox"/> ¹ <input type="checkbox"/>	ATP CLP00
	Regulation 1272/2008 Flam. Liq. 3: H226; STOT SE 3: H336; EUH066 - Warning	
CAS: 77-58-7 EC: 201-039-8 Index: 050-030-00-3 REACH: 01-2119496068-27-XXXX	Dibutyltin Dilaurate <input type="checkbox"/> ¹ <input type="checkbox"/>	ATP ATP10
	Regulation 1272/2008 Muta. 2: H341; Repr. 1B: H360FD; STOT RE 1: H372 - Danger	
CAS: 28660-67-5 EC: 249-134-3 Index: Non-applicable REACH: Non-applicable	Dibutylbis(myristoyloxy)stannane <input type="checkbox"/> ¹ <input type="checkbox"/>	Self-classified
	Regulation 1272/2008 Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Muta. 2: H341; Repr. 1A: H360; STOT RE 2: H373 - Danger	

¹ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

In case of consumption, seek immediate medical assistance showing the SDS for the product.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

- CONTINUED ON NEXT PAGE -

SECTION 5: FIREFIGHTING MEASURES**5.1 Extinguishing media:****Suitable extinguishing media:**

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO₂).

Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES**6.1 Personal precautions, protective equipment and emergency procedures:****For non-emergency personnel:**

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

See section 8.

6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE**7.1 Precautions for safe handling:**

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

SECTION 7: HANDLING AND STORAGE (continued)

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

PREGNANT WOMEN SHOULD NOT BE EXPOSED TO THIS PRODUCT. Transfer in designated areas that comply with the necessary safety conditions (emergency showers and eyewash stations in close proximity), using personal protection equipment, especially on the hands and face (See section 8). Limit manual transfers to small amounts only. Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

- Minimum Temp.: 5 °C
- Maximum Temp.: 25 °C
- Maximum time: 24 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification	Occupational exposure limits		
	N-butyl acetate CAS: 123-86-4 EC: 204-658-1	IOELV (8h)	50 ppm
	IOELV (STEL)	150 ppm	723 mg/m ³

DNEL (Workers):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	11 mg/kg	Non-applicable	11 mg/kg	Non-applicable
	Inhalation	600 mg/m ³	600 mg/m ³	300 mg/m ³	300 mg/m ³
Dibutyltin Dilaurate CAS: 77-58-7 EC: 201-039-8	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	2,08 mg/kg	Non-applicable	0,43 mg/kg	Non-applicable
	Inhalation	0,059 mg/m ³	Non-applicable	0,02 mg/m ³	Non-applicable

DNEL (General population):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	Oral	2 mg/kg	Non-applicable	2 mg/kg	Non-applicable
	Dermal	6 mg/kg	Non-applicable	6 mg/kg	Non-applicable
	Inhalation	300 mg/m ³	300 mg/m ³	35,7 mg/m ³	35,7 mg/m ³

- CONTINUED ON NEXT PAGE -

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Dibutyltin Dilaurate CAS: 77-58-7 EC: 201-039-8	Oral	0,02 mg/kg	Non-applicable	0,003 mg/kg	Non-applicable
	Dermal	0,5 mg/kg	Non-applicable	0,16 mg/kg	Non-applicable
	Inhalation	0,04 mg/m ³	Non-applicable	0,005 mg/m ³	Non-applicable

PNEC:



Identification		Short exposure		Long exposure	
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	STP	35,6 mg/L	Fresh water	0,18 mg/L	
	Soil	0,09 mg/kg	Marine water	0,018 mg/L	
	Intermittent	0,36 mg/L	Sediment (Fresh water)	0,981 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	0,098 mg/kg	
Dibutyltin Dilaurate CAS: 77-58-7 EC: 201-039-8	STP	100 mg/L	Fresh water	0 mg/L	
	Soil	0,041 mg/kg	Marine water	0 mg/L	
	Intermittent	0,005 mg/L	Sediment (Fresh water)	0,05 mg/kg	
	Oral	0,0002 g/kg	Sediment (Marine water)	0,005 mg/kg	

8.2 Exposure controls:



A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection



Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory respiratory tract protection	Filter mask for gases and vapours		EN 405:2002+A1:2010	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands



Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory hand protection	NON-disposable chemical protective gloves		EN ISO 374-1:2016+A1:2018 EN 16523-1:2015+A1:2018 EN 420:2004+A1:2010	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Ocular and facial protection



Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory face protection	Face shield		EN 166:2002 EN 167:2002 EN 168:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection



Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties		EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982-1:2004/A1:2010 EN ISO 6529:2013 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994	For professional use only. Clean periodically according to the manufacturer's instructions.

- CONTINUED ON NEXT PAGE -

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory foot protection	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties		EN ISO 13287:2013 EN ISO 20345:2011 EN 13832-1:2019	Replace boots at any sign of deterioration.

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	100 % weight
V.O.C. density at 20 °C:	880 kg/m ³ (880 g/L)
Average carbon number:	6
Average molecular weight:	116,2 g/mol

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C:	Liquid
Appearance:	Fluid
Colour:	According to the markings on the package
Odour:	Solvent
Odour threshold:	Non-applicable *

Volatility:

Boiling point at atmospheric pressure:	126 - 561 °C
Vapour pressure at 20 °C:	1253 Pa
Vapour pressure at 50 °C:	6144,91 Pa (6,14 kPa)
Evaporation rate at 20 °C:	Non-applicable *

Product description:

Density at 20 °C:	880 kg/m ³
Relative density at 20 °C:	0,88
Dynamic viscosity at 20 °C:	0,75 cP
Kinematic viscosity at 20 °C:	0,85 mm ² /s
Kinematic viscosity at 40 °C:	Non-applicable *
Concentration:	Non-applicable *
pH:	Non-applicable *
Vapour density at 20 °C:	Non-applicable *
Partition coefficient n-octanol/water 20 °C:	Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Solubility in water at 20 °C: Non-applicable *
 Solubility properties: Non-applicable *
 Decomposition temperature: Non-applicable *
 Melting point/freezing point: Non-applicable *

Flammability:

Flash Point: 24 °C
 Flammability (solid, gas): Non-applicable *
 Autoignition temperature: 421 °C
 Lower flammability limit: Not available
 Upper flammability limit: Not available

Particle characteristics:

Median equivalent diameter: Non-applicable

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties: Non-applicable *
 Oxidising properties: Non-applicable *
 Corrosive to metals: Non-applicable *
 Heat of combustion: Non-applicable *
 Aerosols-total percentage (by mass) of flammable components: Non-applicable *

Other safety characteristics:

Surface tension at 20 °C: Non-applicable *
 Refraction index: Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

- CONTINUED ON NEXT PAGE -

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for skin contact. For more information see section 3.
- Contact with the eyes: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.
IARC: Non-applicable
- Mutagenicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with mutagenic effects. For more information see section 3.
- Reproductive toxicity: May damage fertility. May damage the unborn child.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
- Cutaneous: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

F- Specific target organ toxicity (STOT) - single exposure:

Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.
- Skin: Repeated exposure may cause skin dryness or cracking

H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
	LD50 oral	LD50 dermal	
N-butyl acetate	12789 mg/kg		Rat
CAS: 123-86-4	14112 mg/kg		Rabbit
EC: 204-658-1		23,4 mg/L (4 h)	Rat

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Identification	Acute toxicity		Genus
	LD50 oral	LD50 dermal	
Dibutyltin Dilaurate CAS: 77-58-7 EC: 201-039-8	2071 mg/kg	>2000 mg/kg	Rat
Dibutylbis(myristoyloxy)stannane CAS: 28660-67-5 EC: 249-134-3	LC50 inhalation	>20 mg/L	
	LD50 oral	>2000 mg/kg	
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation	>20 mg/L	

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product fails to meet the criteria.

Other information

Non-applicable

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Acute toxicity:

Identification	Concentration		Species	Genus
	LC50	EC50		
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	LC50	Non-applicable		
	EC50	Non-applicable		
	EC50	675 mg/L (72 h)	Scenedesmus subspicatus	Algae
Dibutyltin Dilaurate CAS: 77-58-7 EC: 201-039-8	LC50	262.89 mg/L (96 h)	Danio rerio	Fish
	EC50	Non-applicable		
	EC50	Non-applicable		
Dibutylbis(myristoyloxy)stannane CAS: 28660-67-5 EC: 249-134-3	LC50	>0.1 - 1 (96 h)		Fish
	EC50	>0.1 - 1 (48 h)		Crustacean
	EC50	>0.1 - 1 (72 h)		Algae

Chronic toxicity:

Identification	Concentration		Species	Genus
	NOEC	NOEC		
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	NOEC	Non-applicable		
	NOEC	23.2 mg/L	Daphnia magna	Crustacean

12.2 Persistence and degradability:

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Degradability		Biodegradability	
	N-butyl acetate CAS: 123-86-4 EC: 204-658-1	BOD5	Non-applicable	Concentration
COD		Non-applicable	Period	5 days
BOD5/COD		Non-applicable	% Biodegradable	84 %
Dibutyltin Dilaurate CAS: 77-58-7 EC: 201-039-8	BOD5	0 g O2/g	Concentration	100 mg/L
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	50 %

12.3 Bioaccumulative potential:

Identification	Bioaccumulation potential	
	N-butyl acetate CAS: 123-86-4 EC: 204-658-1	BCF
Pow Log		1.78
Potential		Low
Dibutyltin Dilaurate CAS: 77-58-7 EC: 201-039-8	BCF	31
	Pow Log	3.12
	Potential	Moderate

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
	N-butyl acetate CAS: 123-86-4 EC: 204-658-1	Koc	Non-applicable	Henry
Conclusion		Non-applicable	Dry soil	Non-applicable
Surface tension		2,478E-2 N/m (25 °C)	Moist soil	Non-applicable

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product fails to meet the criteria.

12.7 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Dangerous

Type of waste (Regulation (EU) No 1357/2014):

HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP10 Toxic for reproduction

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2021 and RID 2021:

SECTION 14: TRANSPORT INFORMATION (continued)



- 14.1 UN number or ID number:** UN1263
- 14.2 UN proper shipping name:** PAINT RELATED MATERIAL
- 14.3 Transport hazard class(es):** 3
Labels: 3
- 14.4 Packing group:** III
- 14.5 Environmental hazards:** No
- 14.6 Special precautions for user**
Special regulations: 163, 367, 650
Tunnel restriction code: D/E
Physico-Chemical properties: see section 9
Limited quantities: 5 L
- 14.7 Maritime transport in bulk according to IMO instruments:** Non-applicable

Transport of dangerous goods by sea:

With regard to IMDG 39-18:



- 14.1 UN number or ID number:** UN1263
- 14.2 UN proper shipping name:** PAINT RELATED MATERIAL
- 14.3 Transport hazard class(es):** 3
Labels: 3
- 14.4 Packing group:** III
- 14.5 Marine pollutant:** No
- 14.6 Special precautions for user**
Special regulations: 163, 223, 955, 367
EmS Codes: F-E, S-E
Physico-Chemical properties: see section 9
Limited quantities: 5 L
Segregation group: Non-applicable
- 14.7 Maritime transport in bulk according to IMO instruments:** Non-applicable

Transport of dangerous goods by air:

With regard to IATA/ICAO 2021:



- 14.1 UN number or ID number:** UN1263
- 14.2 UN proper shipping name:** PAINT RELATED MATERIAL
- 14.3 Transport hazard class(es):** 3
Labels: 3
- 14.4 Packing group:** III
- 14.5 Environmental hazards:** No
- 14.6 Special precautions for user**
Physico-Chemical properties: see section 9
- 14.7 Maritime transport in bulk according to IMO instruments:** Non-applicable

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable
Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable
Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable
Article 95, REGULATION (EU) No 528/2012: Non-applicable

SECTION 15: REGULATORY INFORMATION (continued)

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Contains Dibutyltin Dilaurate ; Dibutylbis(myristoyloxy)stannane

Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
P5c	FLAMMABLE LIQUIDS	5000	50000

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Product classified hazardous under the CMR. Sale and distribution to the general public is prohibited. Due to its CMR category, it is essential to apply the specific measures for workplace hazard prevention covered in articles 4 and 5 of the 2004/37/EC Directive and later modifications.

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Contains more than 0.5347 % of Dibutyltin Dilaurate by weight. Dibutylester (DBM) compounds may not be used after 1st January 2012 in mixtures and articles intended for the general public when concentration in said mixture or article or in any part of the same is greater than the equivalent of 0.1 % of tin by weight. Shall not be placed on the market, or used, as substances or in mixtures where the substance or mixture is acting as biocide in free association paint. Shall not be placed on the market, or used, as substances or in mixtures where the substance or mixture acts as biocide to prevent the fouling by micro-organisms, plants or animals of: (a) all craft irrespective of their length intended for use in marine, coastal, estuarine and inland waterways and lakes (b) cages, floats, nets and any other appliances or equipment used for fish or shellfish farming (c) any totally or partly submerged appliance or equipment. Shall not be placed on the market, or used, as substances or in mixtures where the substance or mixture is intended for use in the treatment of industrial waters.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

COMMISSION REGULATION (EU) 2020/878

Texts of the legislative phrases mentioned in section 2:

- H336: May cause drowsiness or dizziness.
- H360FD: May damage fertility. May damage the unborn child.
- H226: Flammable liquid and vapour.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

- Aquatic Acute 1: H400 - Very toxic to aquatic life.
- Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.
- Flam. Liq. 3: H226 - Flammable liquid and vapour.
- Muta. 2: H341 - Suspected of causing genetic defects.
- Repr. 1A: H360 - May damage fertility or the unborn child.
- Repr. 1B: H360FD - May damage fertility. May damage the unborn child.
- STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure.
- STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral).
- STOT SE 3: H336 - May cause drowsiness or dizziness.

- CONTINUED ON NEXT PAGE -

SECTION 16: OTHER INFORMATION (continued)**Classification procedure:**

STOT SE 3: Calculation method

Repr. 1B: Calculation method

Flam. Liq. 3: Calculation method (2.6.4.3)

Advice related to training:

Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:<http://echa.europa.eu><http://eur-lex.europa.eu>**Abbreviations and acronyms:**

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

LC50: Lethal Concentration 50

EC50: Effective concentration 50

LogPOW: Octanolwater partition coefficient

Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -