

Technical Data Sheet

Description:

Cleaner, degreaser and stripper

Usage:

CL 07 is designed for cleaning application equipment and removing fresh and dried drips of water-soluble paint. It effectively degreases unpainted surfaces prior to the application of any type of coating, and enables old coatings to be removed by immersing them in the product for an adequate amount of time.

CL 07 can be applied using a spray gun, brush or cloth. After a short exposure time, wipe the surface with a clean, dry cloth. In the case of heavy soiling, use a clean cloth. After use, rinse the surface with clean water.

This product is not intended for adjusting the viscosity of paints or for degreasing old paint prior to renovation.

CL 07 does not contain hydroxides or acids.

Preparation of CL 07 solution:

When using it as a cleaner and degreaser, dilute the product with water at a ratio of 1:10 (1 part product to 10 parts water). When using it as a remover, do not dilute it.

Colours:

0000-colourless

Specific gravity: (ČSN EN ISO 2811-1)

 $1,09 \pm 0,2$ g/cm3

Application conditions:

Use the protective equipment during greasing and cleaning. Before use read carefully the reccomendations in the safety data sheet. Close a bottle or a canister with CL 07 after use protecting your health and preventing excessive damage to the environment.

Storage:

in the original unopened packaging at temperatures between +5°C and +25°C.

Packaging in I:

1;5

Notes:

DFT - dry film thickness WFT - wet film thickness MS - medium dry matter HS - high dry matter GU - Gloss Unit KU - Krebs unit of viscosity

All information given in this technical data sheet are based on our best knowledge, laboratory test results and practical experience to the date specified below. According to the fact that the conditions of the product's use are out of our control, we can only guarantee the product quality itself. As a producer we cannot be responsible for damage arising from the use of the products without following above recommended instructions or for improper purposes. We reserve the right to change above specified information without prior notice. Always request the actual version of the product data sheet. This technical data sheet replaces all previously released. The validity of the data provided here will be terminated automatically after five years.

VITON s.r.o. Planá 90 370 01 České Budějovice Czech republic



mobil: +42(0) 724 580 404 tel: +42(0) 381 581 022 objednavky@viton.cz www. viton.cz

Issued: 10.06.2025 Revision: C2