



VIR.AC

Technical Data Sheet

Description:

Accelerator

Usage:

Additive is intended for regional retailers, wholesalers and final consumers. It is used to accelerate the drying time of VITON polyurethane coatings PE 33, PE 73 a PE 84. It shortens the curing of applied paint and can be advantageously used at low temperatures between 0-5 ° C. The recommended dosage of the accelerator is 10-20 grams per kilogram of paint. First dose the accelerator to the paint, mix thoroughly with the machine after dosing and after that dose the hardener! When using an accelerator, it is necessary to calculate the half of the pot-life and to take care of the fast processing of the dyed paint and its perfect removal from the application device.

Colours:

0000 - bezbarvý, nažloutlý

Specific gravity: (ČSN EN ISO 2811-1)

0,88 g/cm³

Storage:

in the original unopened packaging at temperatures between +5°C and +25°C.

Packaging in kg:

0,9; 9

Notes:

DFT - dry film thickness
WFT - wet film thickness

MS - medium dry matter
HS - high dry matter

GU - Gloss Unit
KU - Krebs unit of viscosity

All information given in this technical data sheet are based on our best knowledge, laboratory test results and practical experience to the date specified below. According to the fact that the conditions of the product's use are out of our control, we can only guarantee the product quality itself. As a producer we cannot be responsible for damage arising from the use of the products without following above recommended instructions or for improper purposes. We reserve the right to change above specified information without prior notice. Always request the actual version of the product data sheet. This technical data sheet replaces all previously released. The validity of the data provided here will be terminated automatically after five years.

