VIR.MT

Technical Data Sheet

Description:

Matting agent

Usage:

Additive is intended for regional retailers. It is used for reducing a gloss of coatings AE 31, PE 33, KE 30, KE 31 and KE 53. The recommended dosage of the matting agent for coatings AE 31, PE 33, KE 31 and KE 53 is 150 grams per 1 kilogram of paint. For coating KE 30 is the recommended dosage of the matting agent 100grams per 1 kilogram of paint. First dose in the paint the prescribed quantity of pigment pastes according to RAL shade, mix well, then dose the matting agent and mix well once again.

Colours:

bezbarvý

Specific gravity: (ČSN EN ISO 2811-1)

0,88 g/cm3

Solids: (ČSN EN ISO 3251)

by weight	20 %
by volume	17 %

Application conditions:

Matting agent is intended only for the VITOCOLORMIX® tinting system. It cannot be used as a coating material.

Storage:

in the original unopened packaging at temperatures between +5°C and +25°C.

Packaging in kg:

9

Notes:

DFT - dry film thickness	MS - medium dry matter	GU - Gloss Unit
WFT - wet film thickness	HS - high dry matter	KU - Krebs unit of viscosity

All information given in this technical data sheet are based on our best knowledge, laboratory test results and practical experience to the date specified below. According to the fact that the conditions of the product's use are out of our control, we can only guarantee the product quality itself. As a producer we cannot be responsible for damage arising from the use of the products without following above recommended instructions or for improper purposes. We reserve the right to change above specified information without prior notice. Always request the actual version of the product data sheet. This technical data sheet replaces all previously released. The validity of the data provided here will be terminated automatically after five years.

VITON s.r.o.
Planá 90
370 01 České Budějovice
Czech republic

Issued: 15.12.2021

GENUINE CZECH

mobil: +42(0) 724 580 404
tel: +42(0) 381 581 022
objednavky@viton.cz
www. viton.cz